Exclusives are aluminum flagpoles made of cylindrical tube (same diameter at the whole height of the flagpole)

Flag display: Rotating arm on a sleeve revolves according to the wind direction, the flag is always outstretched.



Hoisting and lowering of the flag: Using the hoisting system with a steel rope and crank (for 75 and 93mm diameter)

## TUBE PROFILE: cylindrical aluminum tube with a slot

ANODIZING: 20 microns

WALL THICKNESS: min. 3 mm



## AVAILABLE ACCESSORIES

|   | WEIGHT [kg] |                                      |       |
|---|-------------|--------------------------------------|-------|
| 1 | Alu         | 0,21                                 |       |
|   | 2           | Golden bulb/round finial (brass)     | 0,22  |
|   | 3           | Silver bulb/round finial (aluminum)  | 0,16  |
|   | 4           | Black mushroom shaped top (aluminum) | 0,142 |



|   | WEIGHT [kg]                                 |             |  |
|---|---|-------------|--|
| 1 | Steel rope                                  | 0,02 / mb   |  |
| 2 | Hoisting system with crank                  | 0,086       |  |
| 3 | Flag weight                                 | 1,3         |  |
| 4 | Plastic band (polyethylene)                 | 0,034 / mb  |  |
| 5 | Rotating hoistable banner arm (on a sleeve) | 2,6/3,4/4,1 |  |



|   | WEIGHT [kg]  |           |  |
|---|--|-----------|--|
| 1 | Hinged base plate 75/93 mm<br>(for foundation)   | 7,95/9,55 |  |
| 2 | Portable base (for paving stones sized 50x50cm) installation using the upper part of hinged base plate | 18,6      |  |
| 3 | Ground sleeve 75/93 mm<br>(for foundation)   | 1 / 1,6   |  |



| Height [m]                          | 5                                |    | 6                                |      | 7         |             | 8                                |           | 9                           | 10                             |
|-------------------------------------|----------------------------------|----|----------------------------------|------|-----------|-------------|----------------------------------|-----------|-----------------------------|--------------------------------|
| Number of sections [pcs]            | 1                                |    | 1 1                              |      | 1         |             | 1                                |           | 1                           | 1                              |
| Flagpole diameter (top/bottom) [mm] | 75                               | 93 | 75                               | 93   | 75        | 93          | 75                               | 93        | 93                          | 93                             |
| Net weight without accessories [kg] | 13,2                             | 17 | 15,1                             | 20,3 | 16,8      | 23,7        | 21,1                             | 27,1      | 30,5                        | 33,9                           |
| Recommended size<br>of the flag [m] | 1,2x3,5<br>[4,2 m <sup>2</sup> ] |    | 1,2x3,5<br>[4,2 m <sup>2</sup> ] |      |           |             | 1,2x3,5<br>[4,2 m <sup>2</sup> ] |           | 1,5 x 4 [6 m <sup>2</sup> ] | 1,5 x 4<br>[6 m <sup>2</sup> ] |
| Size of transport package [cm] ±5%  | 560x12x12                        |    | 660x12x12                        |      | 760x12x12 |             | 860x12x12                        |           | 960x12x12                   | 1060x12x12                     |
| + hinged base plate                 | 510x32x30                        |    | 610x32x30 710x3                  |      | 32x30     | 0 810x32x30 |                                  | 910x32x30 | 1010x32x30                  |                                |