

type: TELESCOPIC PORTABLE FLAGPOLE STEP ADJUSTEMENT

Telescopic flagpoles are made of telescopically joined tubes which makes their installation easy and allows to regulate the height of the flagpole.

Flag display:
Rotating plastic cap rotates according to the wind, the flag is always outstretched.

Flag fixing:
banner arm, plastic bands, flag weight

Hoisting/lowering of the flag:
- by raising or putting down the flagpole
- by special round clicks



ALUMINIUM FLAGPOLE

TUBE PROFILE:
telescopically joined aluminum tubes

ANODIZING:
20 microns

WALL THICKNESS:
2 mm



AVAILABLE ACCESSORIES

FINIALS		WEIGHT [kg]
1	Plastic cap with banner arm	0,235



weight without arm



HALYARD SYSTEM		WEIGHT [kg]
1	Flag weight	0,6
2	Plastic band (polyethylene)	0,034 / mb



INSTALLATION ELEMENT		WEIGHT [kg]
1	Car tyre base	1,5
2	Round steel base to use with water ballast	6,15
3	Aluminum ground sleeve 50mm For foundation	0,4
4	Steel base screwed into the ground For installation in soil (ground, mud, sand)	1,48
5	Steel base 48cm x 48cm For outdoor use	15
6	Steel spike hammered into the ground	2,7
7	Polymer concrete base - square 37 x 37 x 6cm	12
8	Polymer concrete base - round Ø 49 x 9cm	16



Height [m]	2,25 - 5,5
Number of sections [pcs]	3
Flagpole diameter (top/bottom) [mm]	50/40/30
Net weight without accessories [kg]	3,9
Recommended size of the flag [m]	1,2 x 2 [2,4 m]
Size of transport package [cm] ±5%	240x10x10