



www.alumast.eu

# type: ALUMINUM SECTIONAL FLAGPOLES

version: STANDARD

Sectional flagpoles are made of 2 or more sections joined together using reduction sleeves

**Flag display:**  
The flag display depends on gusts of wind.



**Flag fixing:**  
rope and hooks  
(attached to the flag)

**Hoisting and lowering of the flag:**  
using an external rope fixed to the belying cleat mounted 1,5m above the ground



ALUMINIUM FLAGPOLE

**TUBE PROFILE:**  
Sectional aluminum

**ANODIZING:**  
20 microns

**WALL THICKNESS:**  
2/2,5mm [5-6m]  
2/2,5/2,5mm [7-10m]  
2/2,5/2,5/3,5mm [11-12m]



## AVAILABLE ACCESSORIES

FINIALS		WEIGHT [kg]
1	Plastic cap	0,06
2	Rotating truck head	0,21
3	Golden bulb/round finial (brass)	0,22
4	Silver bulb/round finial (aluminum)	0,16
5	Plastic cap (option for rotating socket)	0,06



HALYARD SYSTEM		WEIGHT [kg]
1	Rope (polyester or polypropylene)	0,008 /mb
2	Belying cleat	0,026



INSTALLATION ELEMENT		WEIGHT [kg]
1	Ground sleeve 65/80/82,5 mm [5-10 m] (for foundation)	0,5/0,6/0,6
2	Hinged base plate 65/80/82,5/95 mm (for foundation)	6,95/8,15 8,15/9,45
3	Portable base (for paving stones sized 50x50cm) Installation using the upper part of hinged base plate.	18,6



Height [m]	6	8	9	10	12
Number of sections [pcs]	2	3	3	3	4
Flagpole diameter (top/bottom) [mm]	50/65	50/65/80	50/65/80	50/65/80	50/65/80/95
Net weight without accessories [kg]	7,2	12,1	17,1	17,1	22
Recommended size of the flag [m]	1,2x3,5 [4,2 m <sup>2</sup> ]	1,2x3,5 [4,2 m <sup>2</sup> ]	1,5 x 4 [6 m <sup>2</sup> ]	1,5 x 4 [6 m <sup>2</sup> ]	1,5 x 4 [6 m <sup>2</sup> ]
Size of transport package [cm] ±5%	380x8x8	360x14x9	420x14x9	420x14x9	390x18x11
+ hinged base plate	380x32x30	360x32x30	420x32x30	420x32x30	390x32x30